



EM series**PCB MOUNTING SCREW**

Pan head



Bind head



- Self-tapping screws for mounting PCB on bosses or standoffs.
- EM-3-6 self-tapping screws are suitable for mounting 1.6mm or thicker PCB.


Product no. / Details

■ Material / Finish : Steel / Trivalent chromate


Product no.	M	L	Head type	Suitable models	Pack of
EM-1.6	1.6	4	Pan	SMW • CSS • CS SIC • SIM • WC • PS (M1.6 boss models)	50
EM-2	2	5	Pan	PS • TW • TWN • TWF SIC • SIM • PF • WC • WP (M2 boss models)	50
NEW EM-B2	2	5	Bind	SIC • SIM (M2 boss models) SIC • SIM6-12-□ (when installing PCB46-101)	50
EM-2.3	2.3	6	Pan	DRC • WH • LC • LCT • LCS • LCE • PFE WSC (Top cover bosses) PF • PFF (M2.3 boss models) TW • TWN • TWF (M2.3 boss models) WP (M2.3 boss models)	50
EM-2.3-8	2.3	8	Pan	WSC (Bottom base bosses)	50
EM-2.6	2.6	6	Pan	PF • PFF • WP (M2.6 boss models)	50
EM-3	3	5	Pan	SU • OP	50
EM-3-6	3	6	Pan	TWS • TW • TWN • TWF (M3 boss models)	50

MR series**TORX SCREW**

Flat head




Pan head



With pin



★ Without pin




- Self-tapping torx screws for securing of the enclosure.

★ : MR1.6-6S, MR2.6-10□, MR3-5Z□ and MR3-14□ are without pin.

Product no. / Details

★ Mark = Without pin

Product no.	M	L	Head no.	Head style	Material	Finish	Suitable models	Pack of
MR1.6-6S★	1.6	6	T3	Pan	Steel	Nickel plated	CSS • CS	20
MR2.5-8PS	2.5	8	T8	Pan	Steel	Nickel plated	PF • PFE • PFF (M2.5 size)	20
MR2.6-10S★	2.6	10	T8	Flat	Steel	Nickel plated	TW • TWN (M2.6 size)	20
MR2.6-10B★	2.6	10	T8	Flat	Steel	Black trivalent chromate	TWF (M2.6 size)	20
MR2.6-12PS	2.6	12	T8	Pan	Steel	Nickel plated	MX • MXA • MXB • MXF (M2.6 size)	20
MR2.6-14PS	2.6	14	T8	Pan	Steel	Nickel plated	LCT • LCS • LC115-F2 / F3 LCT • LCS • LC145S-F6	20
MR2.6-14S	2.6	14	T8	Flat	Steel	Nickel plated	LCT • LCS • LC115H-F2 / F3 / M2 / 9V LCT • LCS • LC135-F4 / M2 / M3 / 9V LCT • LCS • LC135H-F4 / M2 / M3 / 9V LCT • LCS • LC145-F6 / M2 / M4 LCT • LCS • LC145H-F6 / M2 / M4 LCT • LCS • LC165-M4 LCT • LCS • LC165H-M4	20
MR2.6-18S	2.6	18	T8	Flat	Steel	Nickel plated	LCT • LCS • LC115-N / F2 / F3 LCT • LCS • LC145S-F6 / 145S-N LCE115-N TW • TWN7-2-11 / 7-4-11 / 7-5-11 TWF7-2-11 / 7-4-11 / 7-5-11 / 8-2-8 / 8-4-8	20
MR-1S	3	5	T10	Flat	Steel	Nickel plated	LCT • LCS • LC115H-N / F2 / F3 / M2 / 9V LCT • LCS • LC135-N / F4 / M2 / M3 / 9V LCT • LCS • LC135H-N / F4 / M2 / M3 / 9V LCT • LCS • LC145-N / F6 / M2 / M4 LCT • LCS • LC145H-N / F6 / M2 / M4 LCT • LCS • LC165-N / M4 LCT • LCS • LC165H-N / M4 LCE115H-N • LCE135-N • LCE145H-N • LCE165H-N	20
MR-1B	3	5	T10	Flat	Steel	Black trivalent chromate	UC	20
MR3-5ZS★	3	5	T10	Slotted raised countersunk	Steel	Nickel plated	FC • HY • HYR • HYRH (M3 size)	20
MR3-5ZB★	3	5	T10	Flat	Steel	Black trivalent chromate	CF	20
MR3-8PS	3	8	T10	Pan	Steel	Nickel plated	PF • PFE • PFF (M3 size)	20
MR3-14S★	3	14	T10	Flat	Steel	Nickel plated	TW • TWN (M3 size)	20
MR3-14B★	3	14	T10	Flat	Steel	Black trivalent chromate	TWF (M3 size) MX • MXA • MXB • MXF (M3 size)	20

PFRF series**RUBBER FEET****PFRF dimensions**

■ STP drawings available on our website.


- Recommended to be used with WP series as a desktop-type unit.
- No additional hole milling is required as the rubber feet fits snugly into the screw holes.
- Made from elastomer material.
- Unavailable for use with WP5-7-2, 5-7-3, 6-8-2, and 6-8-3 models.

Product no. / Details

Product no.	Dimensions		Material	Color	Suitable models	Pack of
	A	B				
PFRF-M2.5D	6.4	10	Elastomer UL94HB	Dark gray	WP8-8-2 • 8-8-4 • 8-10-2 • 8-10-4 • 9-13-3 • 9-13-4 • 10-10-3 • 10-10-4 • 11-15-3 • 11-15-4 • 13-18-3 • 13-18-5	4
PFRF-M3D	7.2	11	Elastomer UL94HB	Dark gray	WP15-15-4 • 15-15-6 • 15-21-4 • 15-21-6 • 20-20-5 • 20-20-7 • 20-28-5 • 20-28-7	4

MR series**TORX SCREW**


Head type (with pin)



- Recommended to be used for tamper resistance, or for an elegant look and feel.
- Requires the use of a specialized screwdriver.
- Unavailable for use with WP5-7-2, 5-7-3, 6-8-2, and 6-8-3 models.


Product no. / Details

Product no.	Dimensions		TORX head no.	Material	Finish	Suitable models	Pack of
	M	L					
MR2.5-8ST	2.5	8	T 8 (with pin)	Stainless steel	Unfinished	WP8-8-2 • 8-10-2 • 9-13-3 • 10-10-3 • 11-15-3 • 13-18-3/WSC series	20
MR2.5-16ST	2.5	16	T 8 (with pin)	Stainless steel	Unfinished	WP8-8-4 • 8-10-4 • 9-13-4 • 10-10-4 • 11-15-4 • 13-18-5	20
MR3-8ST	3	8	T 10 (with pin)	Stainless steel	Unfinished	WP15-15-4 • 15-15-6 • 15-21-4 • 15-21-6 • 20-20-5 • 20-20-7 • 20-28-5 • 20-28-7	20


RPS series**PIN SOCKET CONNECTOR for RPCB****RPS dimensions**

■ DXF/DWG/PDF drawings available on our website.

RPS2-2



RPS2-20



■ Material / Color : (Socket) FRPBT UL94V-0 / Black • (Pin) Phosphor bronze

■ 2.54mm hole-to-hole pitch pin socket connector.


Utilize with RPCB expansion PCB for Raspberry Pi series.

Technical Data


Operating temperature : -55°C ~ +105°C
 Rated voltage : DC500V
 Rated current : 1.0A

Product no. / Details

Product no.	Pin layout	Pack of
RPS2-2	4 (2 pin x 2)	1
RPS2-20	40 (20 pin x 2)	1

RPSP2.5-11**HEXAGONAL STANDOFF****RPSP2.5-11 dimensions**

■ DXF/DWG/PDF drawings available on our website.



■ Material / Finish : Brass / Nickel plated

■ Brass hexagonal standoff with M2.5 threads on both male and female sides.

Utilize with RPCB expansion PCB for Raspberry Pi series.

Product no. / Details

Product no.	Pack of
RPSP2.5-11	4

MT2.5-4**MOUNTING SCREW for RPSP2.5-11****MT2.5-4 dimensions**

■ Material / Finish : Steel / Trivalent chromate

■ Utilize when affixing RPCB expansion PCB.


Product no. / Details

Product no.	Pack of
MT2.5-4	4

BFL series**PLASTIC MOUNTING BRACKET**

Color G Color S

- 2 different colored types to match box colors.
- Tough and strong glass fiber filled polycarbonate.

BFL dimensions**Color Type**

Code	Color	Suitable models
G	White gray	BCAP • BCAR
S	Light gray	BCPC • BCPK • BCPR

Components

■ DXF/DWG/PDF drawings available on our website.



Part name	Pcs	Material / Finish
Mounting bracket	4	Glass fiber filled polycarbonate • ABS
Screw	4	Stainless steel / Unfinished

Product no. / Details

Product no.	Suitable models	Screw
BFL-1□	BCAP • R, BCPC • K • R 0912, 1015, 1121, 1126, 1315, 1318, 1621, 1626, 1722, 1727, 212113	Self-tapping M4-12 bind head
BFL-2□	BCAP • R, BCPC • K • R 1928, 2030, 2535, 2828, 2838, 3030, 3040, 3535, 3545, 4050, 4060, 5060	M5-12 bind head
BFL-2-21□	BCAP • R, BCPC • K • R 212110	Self-tapping M4-12 bind head

■ Please suffix color code at the end of the product number.

*Not suitable for BCAP1515 models. Use CK-35P (Stainless steel) instead.

CK series**STAINLESS STEEL MOUNTING BRACKET****CK dimensions****Components**

■ DXF/DWG/PDF drawings available on our website.

Part name	Pcs	Material	Finish
Mounting bracket	4	Stainless steel SUS304	Barrel finish
Screw	4	Stainless steel	Unfinished

Product no. / Details

Product no.	Suitable models	Screw
CK-35P	BCAP • R, BCPC • K • R 0912, 1015, 1121, 1126, 1315, 1318, 1515, 1621, 1626, 1722, 1727, 2121	Self-tapping M4-10 pan head
CK-26P	BCAP • R, BCPC • K • R 1928, 2030, 2535, 2828, 2838, 3030, 3040, 3535, 3545, 4050, 4060	M5-10 pan head

MT series**PCB MOUNTING SCREW**



- PCB mounting screws for inner bosses of BCAP • BCAR • BCPC • BCPK • BCPR series.

**Product no. / Details**

Product no.	Screw details	Material	Finish	Pack of
MT4-8T	Self-tapping M4-8 bind head	Steel	Trivalent chromate	20
MT5-8T	Self-tapping M5-8 bind head	Steel	Trivalent chromate	20

Product no. / Details

Product no.	Suitable models	Recommended torque
MT4-8T	BCAP • R, BCPC • K • R 0912, 1015, 1121, 1126, 1315, 1318, 1515, 1621, 1626, 1722, 1727, 1928, 2121	0.7N • m
MT5-8T	BCAP • R, BCPC • K • R 2030, 2535, 2828, 2838, 3030, 3040, 3535, 3545, 4050, 4060, 5060, 5070, 6080	1.4N • m

MT-3N**SLIDING NUT for EX□ • EXH□****MT-3N dimensions****Product no. / Dimensions**

Product no.	M	L	Material	Finish	Pack of
MT-3N	3	2.4	Steel	Black trivalent chromate	50

- Sliding nut can be used on all EXPT • EXP • EXPE • EXW • EXPF • EXEF • EXWF • EX models with width 140mm or larger bottom covers, as well as with width 230mm and 285mm top covers, on all EXH • EXHE • EXHF • EXHFE models with width 140mm or larger bottom covers, as well as all heat-sink top covers.

EXEG series**EMC SHIELDING FABRIC-OVER-FOAM GASKET**

- Exclusive EMC shielding fabric-over-foam gasket for EXPE • EXEF • EXHE • EXHFE models.

Suitable Models

Product no.	Suitable models
EXEG-2.5	EXPE7-□, 9-□, 12-□, 15-□, EXEF7-□, 9-□, 11-□, 15-□ EXHE8-□, 11-□, 14-□, EXHFE8-□, 11-□, 14-□
EXEG-3.2	EXPE20-□, 24-□, 30-□, EXEF20-□, 24-□ EXHE19-□, 23-□, 29-□, EXHFE19-□, 23-□, 29-□

Product no. / Dimensions

Product no.	Dimensions	Pack of
EXEG-2.5	Φ2.5×500mm	1
EXEG-3.2	Φ3.2×500mm	1

Length tolerance = +/- 10%



- Material / Color : Conductive fiber • TPE / Metallic gray

**EX series APPLICATION EXAMPLE****Tube Amplifier**

Product by MJ Audio Technology

**Premain Power Amplifier**

Product by AY-densi (Japan)

**IoT Relay Module**

Product by Bunnyhop (Japan)

**USB Edge Node**

Product by SHINWA (Japan)



Accessories (Optional parts)

MR SERIES

TORX SCREW KIT



- Material / Finish : Steel / Nickel plated.
- TORX screw kit for CF series x 1 unit.
- Recommended for aesthetic purposes, or for tamper-resistance.
- Requires the use of a specialized screwdriver.

Suitable Enclosures

Product no.	Suitable enclosures
MR-3CS	CF□-11 models
MR-4CS	CF□-18, CF□-23, and CF□-28 models

Product no. / Dimensions

Product no.	Included screws	TORX head no.	Pack of
MR-3CS	M3-10 countersunk x 8 pcs • M3-5 slotted raised countersunk x 4 pcs	T10 (M3)	1 set (for 1 unit)
MR-4CS	M4-12 countersunk x 8 pcs • M3-5 slotted raised countersunk x 4 pcs	T10 (M3) • T20 (M4)	1 set (for 1 unit)

Accessories (Optional parts)

MR SERIES

TORX SCREW



- Material / Finish : Steel / Nickel plated
- TORX screw set for CH series x 1 unit.
- Recommended for aesthetic purposes, or for tamper-resistance.
- Requires the use of a specialized screwdriver.

Suitable Enclosures

Product no.	Suitable enclosures
MR-3CS	CH4 and CH6 models
MR-4CS	CH7 and CH8 models

Product no. / Dimensions

Product no.	Included screws	TORX head no.	Pack of
MR-3CS	M3-10 countersunk x 8 pcs • M3-5 slotted raised countersunk x 4 pcs	T10 (M3)	1 set (for 1 unit)
MR-4CS	M4-12 countersunk x 8 pcs • M3-5 slotted raised countersunk x 4 pcs	T10 (M3) • T20 (M4)	1 set (for 1 unit)

MR SERIES**SLOTTED RAISED COUNTERSUNK TORX SCREW**




- For use with top / bottom cover.
- Recommended for aesthetic purposes, or for tampering resistance.
- Requires the use of a specialized screwdriver.

Product no. / Dimensions

Product no.	M	L	TORX head no.	Material	Color / Finish	Pack of
MR3-5ZS	3	5	T10	Steel	Nickel plated	20
MR3-5ZB	3	5	T10	Steel	Black trivalent chromate	20

EV series**CONDUCTIVE SCREW**

Conductive



Base material exposed after being shaved.



Example: Internal grounding use.




- When tightened, protrusions on the underside of the screw head will shave away at the painted or anodized surface to expose the base material for achieving conductivity.

Product no. / Dimensions

Product no.	M	L	Material	Finish	Suitable series	Pack of
EV3-5S	3	5	Steel	Nickel plated	YM • MB • others	20
NEW EV-4S	4	5	Steel	Nickel plated	BDN • others	20

PLS • MTS • PM series**CAPTIVE FASTENER • CAPTIVE SCREW**PLS-1G
Plastic fastenerMTS-1
Metal fastenerMTS-3
Metal fastener

Hole layout for mounting

**Product no. / Dimensions Fastener**

Product no.	M	Material	Color / Finish	Pack of
PLS-1G	2.5	POM	White gray	50
MTS-1	2.5	Steel	Zinc plated	8
NEW MTS-3	2.5	Steel	Nickel plated	10

Conductive

PM-1□




PM-2□




PM-3


**PM dimensions**

PM-1□ • PM-2□

**Product no. / Dimensions Screw**

Product no.	Material	Finish	L	A	B	Suitable screw driver	Pack of
PM-1B	Steel	Black trivalent chromate	10	4	1.5	#1	50
PM-1S	Steel	Chrome plated	10	4	1.5	#1	50
PM-2B	Steel	Black trivalent chromate	11	5	2	#2	50
PM-2S	Steel	Nickel plated	11	5	2	#2	50
NEW PM-3	Steel	Nickel plated	7	2.5	2	#2	50



TPS series**TAPPING STANDOFF**

■ Tapping screw head allows for easy installation onto existing enclosure boss mount.

■ DXF/DWG/PDF drawings available on our website.

■ 4 different sizes available : M2.3, M2.6, M3 and M4 size.


Product no. / Details

■ Material / Finish : Brass / Unfinished

Product no.	Screw size (a)	Screw size (b)	c	L	ℓ	Weight (g)	Pack of	Suitable models
TPS-M2.3-4	2.3	M2.3	5	4	3	0.7	4	WH series • PFE series LC • LCE • LCS • LCT series PF • PFF series (M2.3 boss models) TW • TWN • TWF series (M2.3 boss models) WP series (M2.3 boss models)
TPS-M2.3-5	2.3	M2.3	5	5	3	0.9	4	
TPS-M2.3-6	2.3	M2.3	5	6	4	1	4	
TPS-M2.3-7	2.3	M2.3	5	7	5	1.2	4	
TPS-M2.3-8	2.3	M2.3	5	8	6	1.3	4	
TPS-M2.3-10	2.3	M2.3	5	10	6	1.7	4	
TPS-M2.3-12	2.3	M2.3	5	12	6	2	4	PF • PFF series (M2.6 boss models) WP series (M2.6 boss models)
TPS-M2.6-4	2.6	M2.6	5	4	3	0.7	4	
TPS-M2.6-5	2.6	M2.6	5	5	3	0.8	4	
TPS-M2.6-7	2.6	M2.6	5	7	5	1.1	4	
TPS-M2.6-10	2.6	M2.6	5	10	6	1.6	4	SU • OP TWS • TW • TWN • TWF series (M3 boss models)
TPS-M2.6-12	2.6	M2.6	5	12	6	2	4	
TPS-M3-4	3	M3	5.5	4	3	0.8	4	
TPS-M3-5	3	M3	5.5	5	3	1.1	4	
TPS-M3-6	3	M3	5.5	6	4	1.2	4	
TPS-M3-7	3	M3	5.5	7	5	1.3	4	
TPS-M3-8	3	M3	5.5	8	5	1.6	4	BCAS • BCAP • BCPC • BCPK series (M4 boss models) BCAR • BCPR series (M4 boss models) SPCP • SPCM • WG • WGV • WGPC
TPS-M3-10	3	M3	5.5	10	6	1.9	4	
TPS-M3-12	3	M3	5.5	12	6	2.3	4	
TPS-M4-6	4	M4	7	6	4	2	4	
TPS-M4-10	4	M4	7	10	6	3.1	4	
TPS-M4-15	4	M4	7	15	8	4.7	4	
TPS-M4-20	4	M4	7	20	10	6.5	4	



■ Please use a suitable sized socket driver to both secure and loosen the tapping standoff.

Installation example**MT** series**PCB MOUNTING SCREWS for TPS**

■ Pan head PCB mounting Screws for TPS tapping standoffs.

Product no. / Details

Product no.	M	L	Material	Finish	Pack of
MT2.3-4	2.3	4	Steel	Trivalent chromate	20
MT2.3-6	2.3	6	Steel	Trivalent chromate	20
MT2.6-4	2.6	4	Steel	Trivalent chromate	20
NEW MT2.6-6	2.6	6	Steel	Trivalent chromate	20
MT3-4	3	4	Steel	Trivalent chromate	20
NEW MT3-6	3	6	Steel	Trivalent chromate	20
NEW MT4-4	4	4	Steel	Trivalent chromate	20
NEW MT4-6	4	6	Steel	Trivalent chromate	20


AST series**INSERT NUT ADHESIVE STANDOFF**

- Double-sided adhesive tape allows the standoff to be mounted quickly and easily; allows PCB mounting in non-boss enclosures.
- Convenient for installing PCBs into enclosures without the need for customization.
- Please ensure that surface is cleaned and grease-free before adhering.
- Once removed, it cannot be adhered on again.


AST dimensions

■ DXF/DWG/PDF/STP drawings available on our website.


AST2.5-□



AST3-□





AST4-□

**Product no. / Details****Bulk package**

Product no	H dimension	Included screw	Recommended PCB thickness (mm)	Recommended torque (N · m)	Weight (g)	Pack of	Product no	Pack of
AST2.5-5B	5	M2.5-5 pan head	1.0 ~ 2.0	0.3	0.6 (1 piece)	4	AST2.5-5B-P	100
AST2.5-10B	10	M2.5-5 pan head	1.0 ~ 2.0	0.3	0.8 (1 piece)	4	AST2.5-10B-P	100
AST3-6B	6	M3-6 pan head	1.0 ~ 3.0	0.4	1.5 (1 piece)	4	AST3-6B-P	100
AST3-10B	10	M3-6 pan head	1.0 ~ 3.0	0.4	1.6 (1 piece)	4	AST3-10B-P	100
AST3-15B	15	M3-6 pan head	1.0 ~ 3.0	0.4	1.8 (1 piece)	4	AST3-15B-P	100
AST3-20B	20	M3-6 pan head	1.0 ~ 3.0	0.4	2.1 (1 piece)	4	AST3-20B-P	100
AST4-10.5B	10.5	M4-8 pan head	1.0 ~ 3.5	0.8	2.6 (1 piece)	4	AST4-10.5B-P	50
AST4-20B	20	M4-8 pan head	1.0 ~ 3.5	0.8	3.2 (1 piece)	4	AST4-20B-P	50

- Base material / color : Nylon 66 (UL94V-2) / Black
- Nut • screw material / finish : Steel / Trivalent chromate

- Bulk packaging is available. See "Bulk package" column above.
- Screws are not included for bulk packages.

ASR series**ADHESIVE PCB STANDOFF****ASR dimensions**

■ DXF/DWG/PDF drawings available on our website.

Technical Data

Recommended torque : 0.4N · m

- M3 tapping screw use adhesive standoff.
Recommended to be used with EM-3 or EM-3-6 self-tapping screws (See page 398).
- Please ensure that surface is cleaned and grease-free before adhering.
- Once removed, it cannot be adhered on again.



Product no. / Details

■ Material / Color: Nylon 66 (UL94V-2) / Natural

Product no	H	h	Weight (g)	Pack of
ASR- 5	5.1	3.1	0.9 (1 piece)	10
ASR- 6	6.4	4.4	1.0 (1 piece)	10
ASR- 7	7.2	5.1	0.9 (1 piece)	10
ASR- 8	8.1	6.3	0.9 (1 piece)	10
ASR- 9	9	7	1.0 (1 piece)	10
ASR-11	11	9	1.0 (1 piece)	10
ASR-13	12.7	10.7	1.2 (1 piece)	10
ASR-14.5	14.7	12.8	1.1 (1 piece)	10
ASR-16	15.9	13.9	1.3 (1 piece)	10
ASR-19	19.1	17.1	1.4 (1 piece)	10





ASL series**LOCKING PCB ADHESIVE STANDOFF**

- Standoff for securing PCB by simply snapping it in.
- Adhesive standoff can be freely and easily affixed on.
- Once removed, it cannot be adhered on again.

ASL-3 ~ 12**ASL-15 & 19****Product no. / Details**


■ Material / Color : PA66 / Natural

Product no.	A	B	Mounting hole	Mounting thickness	Weight (g)	Pack of
ASL- 3	2.7	□14	Φ3	1.2 ~ 1.6	0.5 (1 piece)	10
ASL- 4	4	□14	Φ3	1.2 ~ 1.6	0.5 (1 piece)	10
ASL- 6	5.6	□14	Φ3	1.2 ~ 1.6	0.6 (1 piece)	10
ASL- 7	7.2	□14	Φ3	1.2 ~ 1.6	0.6 (1 piece)	10
ASL- 9	9.2	□14	Φ3	1.2 ~ 1.6	0.6 (1 piece)	10
ASL-10	9.7	□14	Φ3	1.2 ~ 1.6	0.6 (1 piece)	10
ASL-12	11.9	□14	Φ3	1.2 ~ 1.6	0.6 (1 piece)	10
ASL-15	15.4	□20	Φ4	1.2 ~ 1.7	1.3 (1 piece)	10
ASL-19	18.5	□18	Φ4	1.2 ~ 2.0	1.4 (1 piece)	10

APPLICATION EXAMPLE : ASL-3 ~ 12**APPLICATION EXAMPLE : ASL-15 & 19**

RB-9

RUBBER BUSH





- Rubber bush for TMC series terminal junction box.
- Applicable for $\phi 8 \sim \phi 9$ mm diameter cable.

Product no. / Details

Product no.	Material	Color	Cable range	Pack of
RB-9	NBR	Black	$\phi 8 \sim \phi 9$ mm	2

SZ series

WATERPROOF WASHER



- Waterproof washer for screwing onto waterproof boxes.
- NBR sealing material has superior oil resistance (N models only).
- Silicone sealing material has wider operating temperature with superior temperature and water resistance (S models only).

Technical Data

Water pressure resistance :
M3 ~ M16
0.98MPa (10kgf/cm²) / 1 hour

- Shape of the sealing material vary by product.

Product no. / Details

Product no.	W	H	a	b	c	t	Washer material	Sealing material	Color	Screw size	Pack of
SZ- 3N	7	2.7	3.2	2.2	3.1	0.5	SUS304	NBR	Black	M 3	1
SZ- 3S	7	2.7	3.2	2.2	3.1	0.5	SUS304	Silicone	Brown	M 3	1
SZ- 4N	8	2.8	4.2	2.1	4.1	0.5	SUS304	NBR	Black	M 4	1
SZ- 4S	8	2.8	4.2	2.1	4.1	0.5	SUS304	Silicone	Brown	M 4	1
SZ- 5N	9.5	3.6	5.2	2.7	5.1	0.8	SUS304	NBR	Black	M 5	1
SZ- 5S	9.5	3.6	5.2	2.7	5.1	0.8	SUS304	Silicone	Brown	M 5	1
SZ- 6N	11.5	4	6.2	3	6.2	1	SUS304	NBR	Black	M 6	1
SZ- 6S	11.5	4	6.2	3	6.2	1	SUS304	Silicone	Brown	M 6	1
SZ- 8N	15.2	3.8	8.2	3.2	8.2	1	SUS304	NBR	Black	M 8	1
SZ- 8S	15.2	3.8	8.2	3.2	8.2	1	SUS304	Silicone	Brown	M 8	1
SZ-10N	18	5.3	10.2	4	10.2	1.5	SUS304	NBR	Black	M10	1
SZ-10S	18	5.3	10.2	4	10.2	1.5	SUS304	Silicone	Brown	M10	1
SZ-12N	24	6.1	14.2	4.8	12.2	1.5	SUS304	NBR	Black	M12	1
SZ-12S	24	6.1	14.2	4.8	12.2	1.5	SUS304	Silicone	Brown	M12	1
SZ-16N	30	6.8	18.4	5.3	16	1.9	SUS304	NBR	Black	M16	1
SZ-16S	30	6.8	18.4	5.3	16	1.9	SUS304	Silicone	Brown	M16	1
NEW SZ-3N-P	7	2.7	3.2	2.2	3.1	0.5	SUS304	NBR	Black	M 3	50
NEW SZ-3S-P	7	2.7	3.2	2.2	3.1	0.5	SUS304	Silicone	Brown	M 3	50
NEW SZ-4N-P	8	2.8	4.2	2.1	4.1	0.5	SUS304	NBR	Black	M 4	50
NEW SZ-4S-P	8	2.8	4.2	2.1	4.1	0.5	SUS304	Silicone	Brown	M 4	50
NEW SZ-5N-P	9.5	3.6	5.2	2.7	5.1	0.8	SUS304	NBR	Black	M 5	50
NEW SZ-5S-P	9.5	3.6	5.2	2.7	5.1	0.8	SUS304	Silicone	Brown	M 5	50