
Aluminium stud welding

Welded Fasteners

Welded fasteners on aluminium objects.
Standoffs and studs with little surface weld marks can be achieved.






Weld marks may be more visible on plates thinner than 2.0mm.

All dimensions are in mm

All dimensions are in mm



| Part # | Thread code | Thread pitch | a | L +/-0.2 | *Minimum distance |
|-----------|----------------|--------------|-----------|-------------|----------------------|
| AMS-M3-8 | МЗ | 0.5 | 0.8 ± 0.1 | 8 | 7.0 |
| AMS-M3-10 | | | | 10 | |
| AMS-M3-12 | | | | 12 | |
| AMS-M3-15 | | | | 15 | |
| AMS-M4-8 | M4 | 0.7 | 0.8 ± 0.1 | 8 | 7.0 |
| AMS-M4-10 | | | | 10 | |
| AMS-M4-12 | | | | 12 | 7.0 |
| AMS-M4-15 | | | | 15 | |

*Minimum distance = Minimum distance from hole center to edge. Installation requirements vary.

Standoffs Material: Aluminium


| Part # | Thread code | Thread pitch | b | L +/-0.2 | Available screw length | *Minimum distance |
|-----------|----------------|--------------|---|-------------|------------------------|----------------------|
| AFS-M3-5 | М3 | 0.5 | 6 | 5 | 2.0 | 7.0 |
| AFS-M3-6 | | | | 6 | 2.5 | |
| AFS-M3-7 | | | | 7 | 3.5 | |
| AFS-M3-8 | | | | 8 | 4.5 | |
| AFS-M3-9 | | | | 9 | 5.5 | |
| AFS-M4-8 | M4 | 0.7 | 8 | 8 | 3.5 | 7.0 |
| AFS-M4-10 | | | | 10 | 5.5 | |
| AFS-M4-12 | | | | 12 | 7.5 | |

*Minimum distance = Minimum distance from hole center to edge. Installation requirements vary.

Welding



Example



Stainless steel and steel weld fasteners are also available. Please inquire for more details.

Only available together with installation services. Not available separately.